

ECONOMICALLY PRICED

RECHARGEABLE

STORED PRESSURE DESIGN

POLYESTER POWDER EXTERNAL COATING

ALL METAL COMPONENTS

5 YEAR WARRANTY

TEMPERATURE RANGE -0°C to 55°C

MANUFACTURED OF DURABLE HIGH QUALITY MATERIALS

TITAN FOAM Wheeled Fire Extinguishers use AR-SFFF foam at 3-3% solution. This Fluorine-free foam formula provides a blanketing effect that smothers and cools both Class A & B fires, and greatly reduces flashback as it suppresses all vapours.

SPECIFICATIONS

AR-SFFF 3-3 % FOAM

SIZE & CAPACITY KG. (LBS.)	50L	100L
MODEL NUMBER	PSE27-02	PSE27-03
CYLINDER LENGTH (MM.)	875mm	1100mm
CYLINDER WEIGHT (KG.)	32kg	50kg
EXTINGUISHER WEIGHT (KG.)	95kg	160kg
FILLED WEIGHT (KG.)	50kg	100kg
OUTER DIAMETER (MM.)	320mm	406mm
VOLUME (L.)	59L	124L
TEMPERATURE RANGE	-0°C - 55°C	-0°C - 55°C
WORKING PRESSURE (BAR)	15bar	15bar
TEST PRESSURE (BAR)	35bar	35bar
MIN WALL-THICKNESS (MM.)	3.0mm	3.0mm
FIRE CLASS	55A 2BC	55A 3BC



CLASSES OF FIRES	TYPES OF FIRES	PICTURE SYMBOL
A	Wood, paper, cloth, trash & other ordinary materials.	
B	Gasoline, oil, paint, alcohol and other flammable liquids.	

APPROVALS: CE, EN3, ISO 9001



Complies with
EN 1866-1

DISTRIBUTED BY:

InterChem
Just what you need!

INTERCHEM LIMITED
9th Avenue South,
Barataria, Trinidad.
Tel.: (868) 235-CHEM (2436)
Email: sales@interchem.co.tt
Website: www.interchem.co.tt, www.titan.co.tt