



Mobil Special 40 and 50

Added Performance Engine Oil

Product Description

Mobil Special 40 and 50 Series are heavy duty monograde engine oils primarily intended for use in gasoline automotive engines of passenger cars, commercial vehicles and farm equipment. They may also be used in older diesel engines of commercial vehicles and contractor equipment where an API CC engine oil is specified. They are formulated from high quality mineral base oils and an additive system to provide lubrication for combustion engines.

Features and Benefits

- Protection against wear and corrosion.
- Low oil consumption.
- Reduced inventory costs for mixed fleet operations.

Applications

Mobil Special 40 and 50 Series are recommended for the lubrication of gasoline engines for older passenger cars, commercial vehicles and farm equipment where an API SF oil is specified as well as older diesel engines for commercial vehicles and contractor equipment where an API CC oil is specified. They can also be used in gear and hydraulic applications if the builder approves the use of monograde engine oils.

Specifications and Approvals

Mobil Special 40 and 50 are recommended by ExxonMobil for use in applications requiring:	40	50
API SF/CC	X	X

Typical Properties

Mobil Special 40 and 50 properties		
SAE Grade	40	50
Viscosity @ 100°C, cSt, ASTM D 445	15.5	19.6
Total Base Number, mg KOH/g, ASTM 2896	7.1	7.1
Sulfated Ash, wt %, ASTM D 874	0.82	0.82
Flash Point, °C, ASTM D 92	247	241
Pour Point, °C, ASTM D 97	-21	-21

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype and Pegasus design are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

7-2011

ExxonMobil de Colombia S.A.
Calle 90 N° 21-32 , Bogota , Colombia

(571) 628 - 0460

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Copyright © 2001-2016 Exxon Mobil Corporation. All rights reserved.

