



**ROCKSOLID®  
WET LOOK CONCRETE SEALER**

**DESCRIPTION AND USES**

RockSolid® Wet Look Concrete Sealer seals and protects concrete and masonry surfaces from the damaging effects of water, chemicals and UV light. This water-based film-forming formula provides a protective barrier to keep water out, protect against stains and extend the life of the concrete surface. The “wet look” high gloss finish is suitable for use on driveways, patios, walkways, pool decks, basements and more. This product is not intended for use on garage floors.

Wet Look Concrete Sealer is suitable for use on interior or exterior, stained or bare concrete and masonry surfaces. Do not use on asphalt. Wet Look Concrete Sealer is ideal for driveways, walkways, porches, patios, pool decks and more. For ongoing maintenance, surfaces previously sealed with RockSolid Wet Look Concrete Sealer may be sealed again with this product (or another water-base, film-forming sealer).

**PRODUCTS**

SKU	Container Size
317927	1-Gallon Wet Look Concrete Sealer

**PRODUCT FEATURES**

- Seals and protects surface from chemicals & stains
- Excellent water repellency
- Long-lasting formula

**PRODUCT APPLICATION**

**READ ALL INSTRUCTIONS CAREFULLY BEFORE STARTING PROJECT**

**SURFACE PREPARATION**

Proper surface preparation is critical to achieve best results. Allow newly poured concrete to cure for a minimum of 28 days. Sweep away all loose dirt, debris and remove any vegetation that could interfere with application and performance. If necessary, use a wire brush or sander to remove any loose or unsound concrete or masonry. Remove any efflorescence with RockSolid Efflorescence Remover (sold separately). Clean the entire surface, including any oil or grease spots with RockSolid Heavy Duty Cleaner (sold separately). Scrub with a stiff bristle brush or broom. Rinse thoroughly with fresh water. A power washer is preferred. Repeat as necessary to completely clean and rinse. Allow to dry to the touch (typically 4 to 6 hours) before applying RockSolid Wet Look Concrete Sealer.

**PRODUCT APPLICATION (cont.)**

**APPLICATION**

RockSolid Wet Look Concrete Sealer is ready to use. Do not thin. Use only when air (ambient) temperature is between 50-90°F (10-32°C) and the relative humidity is below 85% during the day and night. **Do not apply in direct sunlight.** Do not apply if rain is expected within 24 hours. Use in a well ventilated area.

Mask adjacent surfaces to allow spray application up to all edges. Protect delicate foliage from overspray. Apply using a standard pump sprayer with an adjustable spray tip.\* Stir container to mix product. Fill pump sprayer with product, then fully pressurize the sprayer. Set the spray tip to a medium-fine mist and spray 10-12" from the surface. Do not pour the product on the surface or allow product to puddle.

Start and stop the sprayer just off the work area to prevent drips. For larger areas, work in 6'x6' sections at a time before moving to the next section. Apply the product evenly, using a circular or oval pattern to saturate the surface. Backroll any puddles with a 3/8" to 1/2" nap roller.

For additional protection on heavy traffic areas or for more porous surfaces, wait 4 to 6 hours to recoat. Occasional touch-up or recoat may be necessary for areas subject to heavy foot or vehicle traffic.

\*An alternate method is to apply with a 3/8" or 1/2" nap roller from a paint tray.

**COVERAGE**

Each gallon covers 200-400 square feet (single coat) depending on the porosity of the surface. Porous surfaces may require additional coats.

**DRY TIME**

Dry time is based on 70°F and 50% relative humidity. Allow longer dry time at lower temperatures and higher humidity. Wait a minimum of 4 to 6 hours for light foot traffic. Wait 24-48 hours before returning heavy items, furniture and vehicles. The surface will be fully cured in 72 hours.

**CLEAN-UP**

Wash tools and equipment with soap and water. Properly dispose of all soiled rags and unused product.

**TECHNICAL DATA****ROCKSOLID® WET LOOK CONCRETE SEALER****PHYSICAL PROPERTIES**

<b>Resin Type</b>		Acrylic
<b>Pigment</b>		None
<b>Solvent</b>		Glycol Ethers, Water
<b>Weight</b>	<b>Per Gallon</b>	8.5 lbs.
	<b>Per Liter</b>	1.02 kg
<b>Solids</b>	<b>By Weight</b>	25.7%
	<b>By Volume</b>	23.9%
<b>Volatile Organic Compounds</b>		<100 g/l (0.83lbs./gal.)
<b>Recommended Dry Film Thickness (DFT) per Coat</b>		1.0-2.0 mils (25-50µ)
<b>Practical Coverage at Recommended DFT</b>		200-400 sq.ft./gal. (single coat) Actual coverage will vary depending on the porosity of the surface
<b>Dry Times @ 70-80° F (21-27°C) and 50% Relative Humidity</b>	<b>Touch</b>	1 hour
	<b>Recoat</b>	4-6 hours
	<b>Light Traffic</b>	4-6 hours
	<b>Heavy Items</b>	24-48 hours
<b>Shelf Life</b>		2 years
<b>Flash Point</b>		200°F (93°C)
<b>Safety Information</b>		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.