

CARBON DIOXID

Wheeled Unit

ECONOMICALLY PRICED

RECHARGEABLE

CARBON STEEL CYLINDER

EPOXY POWDER COATED FINISH

ALL METAL COMPONENTS

MANUFACTURED OF DURABLE HIGH QUALIT

5 YEAR WARRANTY



are designed to protect areas where Class B (flammable liquids and gases) or Class C (energized electrical equipment) fires could occur.

They may be used indoors where winds and drafts do not affect discharge or where clean а extinguishing agent is required.

Typical applications include:

- Aviation hangers
- Paint spray booths
- Engine Rooms
- Transformer Rooms
- I.T. Rooms

TY MAT	ERIALS M	a s
CLASSES OF FIRES	TYPES OF FIRES	PICTURE SYMBOL
В	Gasoline, oil, paint and other flammable liquids.	
C	May be used on fires involving live electrical equipment without danger	

to the operator.

		_
SPECIFICATIONS	CO2 WHEE	LED UNITS
SIZE & CAPACITY (KG.)	25	30
CYLINDER LENGTH (MM.)	1330	1370
CYLINDER WEIGHT (KG.)	56	57
EXTINGUISHER WEIGHT (KG.)	110	117
FILLED WEIGHT (KG.)	25	30
OUTER DIAMETER (MM.)	219	232
VOLUME (L.)	40	46
TEMPERATURE RANGE	-30°C - 55°C	-30°C - 55°C
WORKING PRESSURE (BAR)	150	150
TEST PRESSURE (BAR)	225	225
MIN WALL-THICKNESS (MM.)	5.7	5.4
MATERIAL	37MN	37MN
FIRE CLASS	233B	233B

APPROVALS: CE, EN3, ISO 9001



MANUFACTURED TO EXACTING STANDARDS UNDER **OUALITY**







DISTRIBUTED BY:

INTERCHEM LIMITED

- 9th Avenue South, Barataria, Trinidad. Tel.: (868) 638-3800
 - Fax: (868) 638-3801
- Email: mail@interchem.co.tt Website: www.interchem.co.tt, www.titan.co.tt