



MANUFACTURED TO
ACCORDING STANDARD

ANSI

MANUFACTURED TO
ACCORDING STANDARD

OSHA

NOT FOR USE AROUND
ELECTRICITY



PINCH
FREE



Convertible Commercial Ladder | Type II

This versatile ladder can be used in 3 different positions, single/extension, stepladder and staircase, perfect for working on slopes or irregular areas. High performance resistant and innovative tool.



225 LBS.
102 KGS.



PINCH-FREE SPREADERS

Resistant
external
pinch-proof
spreaders



ANTI-SLIP STEPS

Grooves on
every step
secured with
steel rivets



SLIP RESISTANT RUNGS

Anti-slip
trapezoidal
shape rungs



RESISTANT BRACKETS

Resistant bracket
for straight or
extension ladder
function.

POSITIONS



Single or
Extension



Stepladder



Staircase



MODEL



Steps



Ladder Height



Max. Height



Max. Reach



Approx. Spread



Width



LBS/KG
Weight

10439107
(9FT)

17-8'

2,74 m - 9'

4,69 m - 15,4'

4,08 m - 13,4'

1,73 m

0,61 m

24 lbs. - 10,90 kg

10439307
(11FT)

21-10'

3,35 m - 11'

5,30 m - 17,4'

4,69 m - 15,4'

2,15 m

0,67 m

28 lbs. - 12,72 kg