



MANUFACTURED TO  
ACCORDING STANDARD

**ANSI**

MANUFACTURED TO  
ACCORDING STANDARD

**OSHA**

FOR USE AROUND  
ELECTRICITY



**PINCH  
FREE**



### Commercial Stepladder | Type II

Perfect for lightweight (225 lbs.) electric jobs, side rails manufactured with electrically non-conductive reinforced polyester fiberglass. Its multi-functional top allows the user to hold tools and have access to them in a comfortable way. Regular Use.



**225 LBS.**  
**102 KGS.**



#### MULTI-FUNCTIONAL TOP

Top made with high impact polypropylene



#### ANTI-SLIP STEPS

Grooves on every step secured with steel rivets



#### PINCH-FREE SPREADERS

Resistant external pinch-proof spreaders



#### SLIP-RESISTANT FEET

PVC molded anti-slip feet

- ♦ Regular Use
- ♦ Electrically Non-Conductive
- ♦ Corrosion Resistant
- ♦ Easy Storage

### DIMENSIONS

Top: 5-1/2" x 2-1/4"  
Front Rails: 3-1/8" Wide  
Flange: 1-3/16" Wide

Rear Rails: 1-3/4" Wide  
Flange: 1-3/16" Wide  
Rungs: 3" Wide



**MATCH PROFILE COLOR  
FOR LADDER PERFORMANCE**

**225 LBS.**  
**102 KGS.**

**250 LBS.**  
**113 KGS.**

**300 LBS.**  
**136 KGS.**

MODEL	Steps	Ladder Height	Max. Height	Max. Reach	Approx. Spread	Width	LBS/KG Weight
<b>10565407</b> (5FT)	4	1.52 m - 5'	0.90 m - 3'	2.90 m - 9'	0.94 m	0.47 m	10 lbs. - 4.54 kg
<b>10565607</b> (6FT)	5	1.83 m - 6'	1.15 m - 4'	3.15 m - 10'	1.27 m	0.50 m	11 lbs. - 5.00 kg
<b>10565807</b> (8FT)	7	2.44 m - 8'	1.75 m - 6'	3.75 m - 12'	1.46 m	0.55 m	16 lbs. - 7.27 kg