

Last updated: 19/06/2023 10:33:12

CARBON REMOVER 25 LTR

Product group: **651** Product number: **571604**

Unitor™ Carbon Remover™ is a heavy duty solvent based cleaner ideal for removal of stubborn carbon deposits.



Product information

This product supersedes product no: **576793**

Unitor™ Carbon Remover™ is a powerful non-corrosive solvent for quick break down carbon deposits and very economical in use.

Features

- Quickly dissolves deposits containing carbon, resins or varnishes
- Non flammable
- Removes carbon type deposits from burner tips, fuel injectors and all components fouled by carbon, resin or varnishes
- Cleans oil side of fuel heaters, oil coolers, etc.
- Removes carbon based deposits from fuel and lube oil filters
- Can be used for cleaning of: - Pistons - Piston rings - Valve cages

Benefits

- Simple and economical to use
- Eliminates the need for hard scraping

Specification

General

Invent Hazard Material (IMO/EU) classification	C-49
--	------

Physical properties

Appearance	Clear brown
Density [g/ml]	0,99 - 1,00
Flash Point [°C]	Above 61
Form	Liquid
pH	10-11 in 5% solution

Technical data

Not Compatible	Avoid natural and synthetic rubber
----------------	------------------------------------

Documents

[SDoC and MD for IHM](#)

Directions for use

Soak Method

This method is an effective way of cleaning deposits from components and machine parts. In order to reduce the evaporation of Unitor™ Carbon Remover™ both on the pure product as well as on its emulsions, a skin is formed when exposed to air.

The items for cleaning are submerged into the active solvent. A wire basket can be used for small components. Immersion time will depend upon the nature of the deposits to be removed. Light deposits will be removed in 1 hour, whereas heavily oxidised deposits

might need longer time.

The components should be rinsed thoroughly before handling.

Cleaning the Oil Side of Heat Exchangers

The Unitor™ Chemical Cleaning Unit - Product no. 664 737189 - is recommended to be used.

1. Isolate the oil supply, disconnect the heat exchanger oil inlet and outlet, drain off any remaining oil.
2. Connect the discharge side of Unitor™ Chemical Cleaning Unit (CCU) to the lower heat exchanger connection and fit the return to the CCU.
3. Add Unitor™ Carbon Remover™ to the drum, product can be diluted with diesel oil down to 25 % and heat, maintaining the temperature (max 50°C) throughout the cleaning operation. If heating is not available, the cleaning time will need to be extended and a higher product concentration is beneficial.
4. Circulate for 12 hours. When the cleaning is complete, disconnect the lower heat exchanger connection and drain.
5. Connect a high pressure fresh water supply to the upper heat exchanger connection. Rinse until water runs clear.
6. Disconnect, drain and dry.

Related products

Is frequently bought together with

765018	ENVIROCLEAN 25 LTR	571687	DISCLEAN 25 LTR
571356	ROCOR NB LIQUID 25 LTR		
698720	AUTOTREAT - 25 LTR		
571752	NATURAL HANDCLEANER 4X5 LTR		

This page is printed from:

<https://www.wilhelmsen.com/product-catalogue/products/marine-chemicals/cleaning-chemicals/cleaning-and-maintenance/carbon-remover-25-ltr/>