

InterChem

Floor Stripper

Heavy Duty No Scrub, Acrylic Floor Stripper



DILUTIONS:

Heavy Stripping - 1 to 8 (16 oz. per gallon)

Medium Cleaning - 1 to 16 (8 oz. per gallon)

Light Cleaning - 1 to 32 (4 oz. per gallon)

Where to Use: Large strip jobs with heavy build-up of old finishes or urethane fortified finishes.

For Use on:

- ♦ Vinyl Tile
- ♦ Concrete
- ♦ Rubber
- ♦ Asphalt Tile
- ♦ Vinyl Asbestos

DESCRIPTION: Heavy duty no scrub, pleasantly scented, floor stripper. Quickly liquefies finish for easy removal. High dilution, super aggressive for the toughest strip outs.

Read Instructions Before Use.

DIRECTIONS: Dust mop and scrape gum, etc. from floor. Determine dilution from table above and add appropriate amount of product to cool or room temperature water. If cold water must be used, allow additional dwell time. Apply solution generously to a workable area. Allow solution to sit for 5-10 minutes. Floor must remain wet if not using a stripping machine.

The only agitation necessary will be from mopping action when applying the stripper. For heavy build up, agitate solution with a floor machine using an aggressive stripping pad (black or brown) if needed, hand scrub edges and corners with an edge pad or center of the scrubbing pad. Pick up solution and old finish with a wet vac or mop and bucket. Inspect the entire floor to ensure that complete stripping has been accomplished. Reapply where necessary. Rinse thoroughly with cool, clear water. Allow floor to dry completely prior to applying sealer or finish.

Technical Specifications

COLOR:Transparent Purple	VISCOSITY:Water Thin
FORM:Liquid	STORAGE(Unopened):...1 Year @R.T.
SCENT:Slight solvent	BIODEGRADABLE:Yes
pH:13.6	WEIGHT/GAL:8.4
FLASH POINT: .None	SHIPPING CLASS:8, packing Gr III
FOAM:Low	PACKAGING:4x1, 5 gal, 55 gal
TYPE:.....Heavy Duty No Scrub Floor Finish Stripper	

4-STEP FLOORCARE PROGRAM

STEP 1 STRIP HEAVY DUTY NO SCRUB, ACRYLIC FLOOR STRIPPER

Useful Tip: For best results, apply with a dry cotton mop. For heavier jobs, use a low speed stripping machine.

STEP 2 SEAL ACRYLIC POLYMER FLOOR SEALER

Useful Tip: For best results, apply 2 coats with a dry rayon string mop, allowing sealer to dry completely between coats.

STEP 3 POLISH NON SLIP FAST DRYING, FLOOR FINISH/POLISH

Useful Tip: For best results, apply 4 coats in a figure-eight motion, with dry rayon string mop. Do not use fans to dry.

STEP 4 MAINTAIN LEMON SCENT/NO-RINSE FORMULA, ALL-PURPOSE NEUTRAL CLEANER

Useful Tip: Thoroughly mop and rinse floor with water, changing the mopping solution frequently

MADE IN THE U.S.A.

Packaged & Distributed by:

Interchem Limited, 9th Avenue South, Barataria, Trinidad. Tel.: (868) 638-3800

InterChem

Floor Sealer

Acrylic Polymer Floor Sealer



DILUTIONS:

DO NOT THIN. Use as is.

Where to Use:

For all types of floor finishes.

For Use on:

- ◆ Asphalt Tile
- ◆ Linoleum
- ◆ Vinyl Tile
- ◆ Sealed Wood
- ◆ Vinyl Asbestos

DESCRIPTION: An acrylic floor sealer with superior bonding and leveling qualities. This high quality undercoating increases depth of gloss and provides for a longer wearing finish.

Read Instructions Before Use.

DIRECTIONS: Prior to application, floor should be completely stripped of all old finishes. Follow stripping procedures from the Floor Care Manual. Apply two coats of Floor Sealer, allowing adequate drying time between coats. After second coat has dried completely, start the finish process. Be sure to use a different mop for sealing and finishing.

Technical Specifications

COLOR:	Hazy-white	TYPE:	Acrylic Polymer Sealer
FORM:	Liquid	SOLID CONTENT:	18%
SCENT:	Odorless	INITIAL GLOSS:	Good
pH:	8.0	RECOAT DRYING TIME:....	30 Minutes
FLASH POINT:	None	COVERAGE:	2500 sq. ft.
FOAM:	None	LEVELING:	Good
VISCOSITY:	Water Thin	SLIP COEFFICIENT:.....	0.5
STORAGE(Unopened):	1 Year @R.T.	REMOVABILITY:.....	Good
BIODEGRADABLE:....	Yes	SCUFF RESISTANCE:.....	Good
WEIGHT/GAL:	8.5	DETERGENT RESISTANT: .	Excellent
SHIPPING CLASS:.....	None	HIGH SPEED BURNISH:....	No
PACKAGING:	4x1, 5 gal, 55 gal		

4-STEP FLOORCARE PROGRAM

STEP 1 STRIP

HEAVY DUTY NO SCRUB, ACRYLIC FLOOR STRIPPER

Useful Tip: For best results, apply with a dry cotton mop. For heavier jobs, use a low speed stripping machine.

STEP 2 SEAL

ACRYLIC POLYMER FLOOR SEALER

Useful Tip: For best results, apply 2 coats with a dry rayon string mop, allowing sealer to dry completely between coats.

STEP 3 POLISH

NON SLIP FAST DRYING, FLOOR FINISH/POLISH

Useful Tip: For best results, apply 4 coats in a figure-eight motion, with dry rayon string mop. Do not use fans to dry.

STEP 4 MAINTAIN

LEMON SCENT/NO-RINSE FORMULA,
ALL-PURPOSE NEUTRAL CLEANER

Useful Tip: Thoroughly mop and rinse floor with water, changing the mopping solution frequently

MADE IN THE U.S.A.

Packaged & Distributed by:

Interchem Limited, 9th Avenue South, Barataria, Trinidad. Tel.: (868) 638-3800

InterChem

Floor Finish/Polish

Non-Slip Fast Drying Finish



DILUTIONS:

DO NOT THIN. Use as is.

For Use on:

- Vinyl Tile
- Linoleum
- Terrazo
- Asphalt Tile
- Concrete
- Rubber
- Sealed Wood
- Asbestos Tile

DESCRIPTION: A highly versatile extended wear metal cross linked floor sealer/finish with 25% solids. Formulated with exclusive micro molecular technology for easy maintenance, high gloss, exceptional film clarity and outstanding "off the mop gloss".

Read Instructions Before Use.

DIRECTIONS: Prior to application, floor should be completely stripped of all old finish, scrubbed or cleaned. Follow stripping procedure from the Floor Care Manual. The floor should be completely dry before applying first coat and all subsequent coats. Apply in thin coats, evenly. If floor is old or in poor condition, two coats of Floor Sealer is recommended. Then apply finish. On unsealed floors, apply 4-5 coats.

On cleaned or scrubbed floors, apply as needed. Be sure to use a different mop for stripping, sealing and finish. Allow 24 hours for curing before burnishing.

Technical Specifications

COLOR: Milk-white	TYPE: Acrylic Polymer
FORM: Liquid	SOLID CONTENT: 25%
SCENT: Mild Solvent/Polymer	INITIAL GLOSS: High
pH: 8.0	RECOAT DRYING TIME: <30 Minutes
FLASH POINT: None	COVERAGE: 2500 - 3000 sq. ft.
FOAM: None	LEVELING: Excellent
VISCOSITY: Water Thin	SLIP COEFFICIENT: 0.57
STORAGE(Unopened): . 1 Year @R.T.	REMOVABILITY: Excellent
BIODEGRADABLE: Yes	SCUFF RESISTANCE: Very Good
WEIGHT/GAL: 8.5	DETERGENT RESISTANT: . Very Good
SHIPPING CLASS: None	HIGH SPEED BURNISH: Yes
PACKAGING: 4x1, 5 gal, 55 gal	

4-STEP FLOORCARE PROGRAM

STEP 1 STRIP

HEAVY DUTY NO SCRUB, ACRYLIC FLOOR STRIPPER

Useful Tip: For best results, apply with a dry cotton mop. For heavier jobs, use a low speed stripping machine.

STEP 2 SEAL

ACRYLIC POLYMER FLOOR SEALER

Useful Tip: For best results, apply 2 coats with a dry rayon string mop, allowing sealer to dry completely between coats.

STEP 3 POLISH

NON SLIP FAST DRYING, FLOOR FINISH/POLISH

Useful Tip: For best results, apply 4 coats in a figure-eight motion, with dry rayon string mop. Do not use fans to dry.

STEP 4 MAINTAIN

LEMON SCENT/NO-RINSE FORMULA,
ALL-PURPOSE NEUTRAL CLEANER

Useful Tip: Thoroughly mop and rinse floor with water, changing the mopping solution frequently

MADE IN THE U.S.A.

Packaged & Distributed by:

Interchem Limited, 9th Avenue South, Barataria, Trinidad. Tel.: (868) 638-3800

InterChem

All-Purpose Neutral Cleaner

Lemon Scent/No-Rinse Formula



DILUTIONS:

Damp Mop - 1 to 2 ounces per gallon

Light Cleaning - 1 ounce per gallon

Regular Cleaning - 2 ounces per gallon

Heavy Duty Cleaning - 4 ounces per gallon

For Use on:

- ◆ Asphalt Tile
- ◆ Linoleum
- ◆ Countertops
- ◆ Sinks
- ◆ Rubber Tile
- ◆ Terrazo
- ◆ Tables
- ◆ Formica®
- ◆ Vinyl Tile
- ◆ Concrete
- ◆ Walls
- ◆ Sealed Wood Surfaces

DESCRIPTION: A lemon-scented, no-rinse, neutral pH, all-purpose cleaner and floor cleaner, formulated to safely clean surfaces and floors, without dulling or removing the protective finish. It quickly removes and emulsifies soils for easy cleaning.

Read Instructions Before Use.

DIRECTIONS: Floor Cleaning: Dust mop floor prior to cleaning. Remove any gum or other foreign material. Dilute product into a mop bucket according to the directions above. Use a clean mop or floor scrubber to apply the solution to the floor. If using a mop, wring mop out and pick up excess solution. Rinsing is not necessary. When solution becomes dirty, a new solution should be made.

All-Purpose Cleaning: Dilute product into a bucket or spray bottle according to the directions above. Spray the surface lightly or dampen a sponge, paper towel or cloth. Agitate with sponge or rag and wipe clean.

Technical Specifications

COLOR: Yellow
FORM: Liquid
SCENT: Lemon
pH: 8.7 +/- 0.5
FLASH POINT: None
FOAM: Low

VISCOSITY: Water Thin
STORAGE(Unopened):...2 Years @R.T.
BIODEGRADABLE: ...Yes
WEIGHT/GAL:8.4 Lbs.
SHIPPING CLASS:None
PACKAGING:4x1, 5 gal, 55 gal

4-STEP FLOORCARE PROGRAM

STEP 1 STRIP

HEAVY DUTY NO SCRUB, ACRYLIC FLOOR STRIPPER

Useful Tip: For best results, apply with a dry cotton mop. For heavier jobs, use a low speed stripping machine.

STEP 2 SEAL

ACRYLIC POLYMER FLOOR SEALER

Useful Tip: For best results, apply 2 coats with a dry rayon string mop, allowing sealer to dry completely between coats.

STEP 3 POLISH

NON SLIP FAST DRYING, FLOOR FINISH/POLISH

Useful Tip: For best results, apply 4 coats in a figure-eight motion, with dry rayon string mop. Do not use fans to dry.

STEP 4 MAINTAIN

LEMON SCENT/NO-RINSE FORMULA,
ALL-PURPOSE NEUTRAL CLEANER

Useful Tip: Thoroughly mop and rinse floor with water, changing the mopping solution frequently

MADE IN THE U.S.A.

Packaged & Distributed by:

Interchem Limited, 9th Avenue South, Barataria, Trinidad. Tel.: (868) 638-3800