

# T-Rex Grab Drywall Adhesive

## Safety Data Sheet



# T-Rex Grab Drywall Adhesive

## Safety Data Sheet

Issue date: 05/24/2024 Revision date: 05/24/2024 Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : T-Rex Grab Drywall Adhesive

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use/Consumer use  
Use of the substance/mixture : adhesives

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Soudal  
350 Ring Road  
Elizabethtown, KY 42701  
Phone: (270) 769-3385  
[Technical@soudalaccumetric.com](mailto:Technical@soudalaccumetric.com)  
[www.SoudalUSA.com](http://www.SoudalUSA.com)

#### 1.4. Emergency telephone number

ChemTrec: (800) 424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification

Not classified

##### Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

#### 2.2. Label elements

Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1).

#### 2.3. Other hazards

The product does not meet the PBT and vPvB classification criteria

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

# T-Rex Grab Drywall Adhesive

## Safety Data Sheet

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	Classification
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5	< 0.05	Acute Tox. 4 (Oral), H302 (ATE=490 mg/kg bodyweight) Acute Tox. 2 (Inhalation:gas), H330 (ATE=100 ppmv/4h) Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411 (M=1)
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS-No.: 55965-84-9	< 0.0015	Acute Tox. 2 (Inhalation), H330 (ATE=0,05 mg/l/4h) Acute Tox. 2 (Dermal), H310 (ATE=50 mg/kg bodyweight) Acute Tox. 3 (Oral), H301 (ATE=66 mg/kg bodyweight) Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Respiratory problems: consult a doctor/medical service.
First-aid measures after skin contact	: Wash skin with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist if irritation persists.
First-aid measures after ingestion	: Rinse mouth out with water. Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

No additional information available

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide. Unsuitable extinguishing media : None known.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

# T-Rex Grab Drywall Adhesive

## Safety Data Sheet

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Large spills: scoop solid spill into closing containers. Clean contaminated surfaces with an excess of water. Wash clothing and equipment after handling.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Keep away from naked flames/heat.

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Store at room temperature. Protect against frost. Keep container tightly closed.

Incompatible products : Heat sources.

Maximum storage period : 1 year

Packaging materials : Synthetic material.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

No additional information available

# T-Rex Grab Drywall Adhesive

## Safety Data Sheet

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment symbol(s):



#### 8.2.2.1. Eye and face protection

##### Eye protection:

Safety glasses

#### 8.2.2.2. Skin protection

##### Skin and body protection:

Wear suitable protective clothing

##### Hand protection:

Protective gloves

#### 8.2.2.3. Respiratory protection

##### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

**Environmental exposure controls:** Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Color	: White
Appearance	: Pasty.
Odor	: characteristic.
Odor threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available

# T-Rex Grab Drywall Adhesive

## Safety Data Sheet

Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapor pressure	: Not available
Vapor pressure at 50°C	: Not available
Density	: 1.3 g/ml
Relative density	: Not available
Relative vapor density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

VOC content : 1 % (14g/l)

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Keep away from naked flames/heat.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

### 1,2-benzisothiazol-3(2H)-one (2634-33-5)

# T-Rex Grab Drywall Adhesive

## Safety Data Sheet

LD50 oral rat	490 mg/kg bodyweight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))

### reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)

LD50 oral rat	66 mg/kg bodyweight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Calculated by reference to active substance, Oral, 14 day(s))
LD50 oral	59 mg/kg bodyweight
LD50 dermal rat	> 141 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 14 day(s))
LD50 dermal	> 75 mg/kg bodyweight
LC50 Inhalation - Rat	0,17 mg/l air (OECD 403: Acute Inhalation Toxicity, 4 h, Rat, Male / female, Experimental value, Calculated by reference to active substance, Inhalation (aerosol), 14 day(s))

Skin corrosion/irritation : Not classified

### 1,2-benzisothiazol-3(2H)-one (2634-33-5)

pH	No data available in the literature
<b>reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)</b>	
pH	No data available in the literature

Serious eye damage/irritation : Not classified

### 1,2-benzisothiazol-3(2H)-one (2634-33-5)

pH	No data available in the literature
<b>reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)</b>	
pH	No data available in the literature

Respiratory or skin sensitisation : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified  
STOT-single exposure : Not classified  
STOT-repeated exposure : Not classified  
Aspiration hazard : Not classified

### 1,2-benzisothiazol-3(2H)-one (2634-33-5)

Viscosity, kinematic	Not applicable (solid)
----------------------	------------------------

# T-Rex Grab Drywall Adhesive

## Safety Data Sheet

### reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)

Viscosity, kinematic	No data available in the literature
----------------------	-------------------------------------

### 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Not rapidly degradable

### 1,2-benzisothiazol-3(2H)-one (2634-33-5)

LC50 - Fish [1]	2,18 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	2,94 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Experimental value, Lethal)
ErC50 algae	150 µg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Experimental value, GLP)

### reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)

LC50 - Fish [1]	0,19 mg/l
EC50 - Crustacea [1]	0,007 mg/l (48 h, Acartia tonsa, Salt water, Experimental value, GLP)
EC50 - Other aquatic organisms [1]	0,126 mg/l waterflea
EC50 - Other aquatic organisms [2]	0,003 mg/l

### 12.2. Persistence and degradability

#### 1,2-benzisothiazol-3(2H)-one (2634-33-5)

Persistence and degradability	Not biodegradable.
-------------------------------	--------------------

### reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)

Persistence and degradability	Not biodegradable.
-------------------------------	--------------------

### 12.3. Bioaccumulative potential

#### 1,2-benzisothiazol-3(2H)-one (2634-33-5)

BCF - Fish [1]	6,62 (Equivalent or similar to OECD 305, 56 day(s), Lepomis macrochirus, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	-0,9 – 0,99 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)

# T-Rex Grab Drywall Adhesive

## Safety Data Sheet

Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
---------------------------	--

### reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)

BCF - Fish [1]	41 – 54 (OECD 305: Bioconcentration: Flow-Through Fish Test, 28 day(s), Lepomis macrochirus, Flow-through system, Fresh water, Experimental value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	0,75 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 24 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

### 12.4. Mobility in soil

#### 1,2-benzisothiazol-3(2H)-one (2634-33-5)

Surface tension	72,6 mN/m (20 °C, 0.1 %, EU Method A.5: Surface tension)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0,97 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Ecology - soil	Highly mobile in soil.

### reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0,81 – 1 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

### 12.5. Results of PBT and vPvB assessment

#### T-Rex Grab Drywall Adhesive

The product does not meet the PBT and vPvB classification criteria

### 12.6. Endocrine disrupting properties

No additional information available

### 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Regional legislation (waste)	: Non-hazardous waste.
Waste treatment methods	: We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.
Sewage disposal recommendations	: Do not discharge into drains or the environment.
Ecology - waste materials	: Avoid release to the environment.



# T-Rex Grab Drywall Adhesive

## Safety Data Sheet

### SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.2. UN proper shipping name</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.3. Transport hazard class(es)</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.4. Packing group</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.5. Environmental hazards</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Not regulated

#### Transport by sea

Not regulated

#### Air transport

Not regulated

#### Inland waterway transport

Not regulated

#### Rail transport

Not regulated

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### 15.1.1. US Federal Regulations

###### TSCA

All components of this product follow the inventory listing requirements of the US Toxic Substances and Control Act (TSCA) Chemical Substances Inventory.

SARA 311 and 312: No SARA hazards.

# T-Rex Grab Drywall Adhesive

## Safety Data Sheet

---

SARA 313: This material does not contain any chemicals with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### 15.1.2. US State Regulations

#### Pennsylvania Right to Know

1,2 benzothiazol-3(2H)-one 2634-33-5

#### Massachusetts Right to Know

1,2 benzothiazol-3(2H)-one 2634-33-5

#### New Jersey Right to Know

1,2 benzothiazol-3(2H)-one 2634-33-5

#### California Prop 65:

WARNING: This product can expose you to titanium dioxide, which is known to the State of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## SECTION 16: Other information

Disclaimer: The data contained herein is based upon information that Soudal believes to be reliable. Users of this product have the responsibility to determine the suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.