



# SOUDAL

## Safety Data Sheet

### SOUDAL Gun & Foam Cleaner

#### Section 1. Identification

Product Identifier SOUDAL Gun & Foam Cleaner  
Synonyms 902000  
Manufacturer Stock Numbers 1203119

Recommended use Refer to Technical Information  
Uses advised against Refer to Technical Information

Manufacturer Contact  
Address Soudal  
350 Ring RD  
Elizabethtown, KY, 42701  
USA

Phone  
(270) 769-3385

Emergency Phone  
(800) 424-9300  
CHEMTREC

Fax  
(270) 765-2412

#### Section 2. Hazards Identification

Classification FLAMMABLE AEROSOLS - Category 1  
SERIOUS EYE DAMAGE /EYE IRRITATION - Category 2A  
SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure) - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (Single Exposure) - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (Single Exposure) - Category 3  
TOXIC TO REPRODUCTION - Category 2

Signal Word Danger

## Pictogram



## Hazard Statements

Causes serious eye irritation  
Extremely flammable aerosol  
May cause damage to organs (heart, respiratory tract, central nervous system).  
May cause damage to organs through prolonged or repeated exposure (blood)  
May cause respiratory irritation. May cause drowsiness or dizziness  
Suspected of damaging fertility or the unborn child.

## Precautionary Statements

### Response

Call a poison center/doctor if you feel unwell.  
Get medical advice/attention if you feel unwell.  
If exposed or concerned: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If inhaled: Remove person to fresh air and keep comfortable for breathing.

### Prevention

Do not breathe fume, mist, vapors, spray.  
Do not eat, drink or smoke when using this product.  
Do not handle until all safety precautions have been read and understood.  
Do not spray on an open flame or other ignition source.  
Keep away from heat/sparks/open flame/hot surfaces - No smoking.  
Obtain special instructions before use.  
Pressurized container: Do not pierce or burn, even after use.  
Use only outdoors or in a well-ventilated area.  
Wash thoroughly after handling.  
Wear eye protection/face protection.  
Wear protective gloves/protective clothing/eye protection/face protection.

### Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
Store in a well-ventilated place. Keep container tightly closed.  
Store locked up.

### Disposal

Dispose of contents/container in accordance with local/regional/national /international regulations.

Ingredients of unknown toxicity 0%

Hazards not Otherwise Classified

Other hazards None known

## Section 3. Ingredients

CAS

Ingredient Name

Weight %

67-64-1	2-Propanone	50% - 75%
75-28-5	Isobutane	10% - 20%
74-98-6	Propane	10% - 20%

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First-Aid Measures

Description of necessary measures	IF exposed or concerned: Get medical advice/attention; Call a POISON CENTER or doctor/physician. Get medical advice/attention if you feel unwell.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
Skin	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.
Eyes	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER or doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.
Ingestion	If a large amount is swallowed, get medical attention.
Indication of any immediate medical attention and special treatment needed	Treat symptomatically and supportively.
Most Important Symptoms/Effects	Acute Causes serious eye irritation. May cause damage to organs. May cause respiratory irritation. May cause drowsiness or dizziness.  Delayed Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

## Section 5. Fire Fighting Measures

Suitable Extinguishing Media	Use carbon dioxide, regular dry chemical, regular foam or water.
Unsuitable Extinguishing Media	None known
Special Hazards Arising from the Chemical	Extremely flammable aerosol. Pressurized container: may burst if heated. Vapors are heavier than air and may travel a considerable distance to a source of ignition and flashback. Vapor/air mixtures are explosive. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.
Hazardous Combustion Products	Oxides of carbon, carbon monoxide
Special Protective Equipment and Precautions for Firefighters	Wear self-contained breathing apparatus with a full facepiece and protective clothing. Avoid inhalation of material or combustion by-products. Move container from fire area if it can be done without risk.
Fire Fighting Measures	Move container from fire area if it can be done without risk. Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out.

Stay away from the ends of tanks. For fires in cargo or storage area: If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For tank, rail car or tank truck: Stop leak if possible without personal risk. Let burn unless leak can be stopped immediately. For smaller tanks or cylinders, extinguish and isolate from other flammables. Evacuation radius: 800 meters (1/2 mile). Do not attempt to extinguish fire unless flow of material can be stopped first. Flood with fine water spray. Cool containers with water spray until well after the fire is out. Apply water from a protected location or from a safe distance. Stay upwind and keep out of low areas. Evacuate if fire gets out of control or containers are directly exposed to fire. 500 meters (1/3 mile). Consider downwind evacuation if material is leaking.

## Section 6. Accidental Release Measures

### Personal Precautions, Protective Equipment and Emergency Procedures

Safe handling: see section 7. See Section 8 for personal protection information. Keep unnecessary people away, isolate hazard area and deny entry. Avoid contact with skin and eyes.

### Methods and Materials for Containment and Cleaning Up

Avoid heat, flames, sparks and other sources of ignition. Do not spray on an open flame or other ignition sources. Pressurized container: Do not pierce or burn, even after use. Stop leak if possible without personal risk. Only personnel trained for the hazards of this material should perform clean up and disposal. Use non-sparking tools and equipment.

### Environmental Precautions

Do not flush into sanitary sewer systems, drains or surface water. Avoid release to the environment.

## Section 7. Handling and Storage

### Precautions for Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flame/hot surfaces - No smoking. Do not pierce or burn, even after use. Do not spray on an open flame or other ignition sources. Use only outdoors or in a well-ventilated area. Wear protective eye/face protection. Do not breathe dust/fume/gas/mist /vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product.

### Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed Store locked up Protect from sunlight. Do not expose to temperatures exceeding 50C/122F

### Incompatible Materials

oxidizing materials, bases, combustible materials, strong acids

## Section 8. Exposure Controls/Personal Protection

### Occupational Exposure Limits

Ingredient Name	ACGIH TLV	OSHA PEL	STEL
2-Propanone	500 ppm TWA	1000 ppm TWA	750 ppm

Isobutane	1000 ppm	N/A	1000 ppm
Propane	1000 ppm TWA	1000 ppm PEL	N/A

Personal Protective Equipment  
Biological limit value  
Engineering Controls

Goggles, Gloves

There are no biological limit values for any of this product's components. Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin Protection

Wear appropriate chemical resistant clothing.

Respiratory Protection

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Glove Recommendations

Wear appropriate chemical resistant gloves.

## Section 9. Physical and Chemical Properties

Physical State	Aerosol
Color	Colorless
Odor	Acetone
Odor Threshold	Not available
Solubility	Insoluble in water
Partition coefficient Water/n-octanol	Not available
VOC%	N/A
Viscosity	Not available
Specific Gravity	N/A
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	Not available
FP Method	N/A
pH	Not available
Melting Point	Not available
Boiling Point	Not available
Boiling Range	N/A
LEL	1.5
UEL	12.5
Evaporation Rate	Not available

Flammability	Not available
Decomposition Temperature	Not available
Auto-ignition Temperature	Not available
Vapor Pressure	Not available
Vapor Density	Not available

**Note** The above information is not intended for use in preparing product specifications. Contact Soudal before writing specifications.

## Section 10. Stability and Reactivity

Reactivity	None known.
Chemical Stability	Stable under normal conditions of use.
Possibility of Hazardous Reactions	Hazardous polymerization will not occur.
Conditions to Avoid	Avoid contact with incompatible materials. Avoid heat, flames, sparks and other sources of ignition.
Incompatible Materials	oxidizing materials, bases, combustible materials, strong acids, halogens
Hazardous decomposition products	oxides of carbon, carbon monoxide

## Section 11. Toxicological Information

Information on Likely Routes of Exposure	Inhalation May cause respiratory irritation.
	Skin Contact No information on significant adverse effects.
	Eye Contact Causes serious eye irritation.
	Ingestion No information on significant adverse effects.
Component Analysis - LD50/LC50	The components of this material have been reviewed in various sources and the following selected endpoints are published: Acetone (67-64-1) Inhalation LC50Rat 50100 mg/m <sup>3</sup> 8 h
	Propane (74-98-6) Inhalation LC50Rat 658 mg/L 4 h
	Isobutane (75-28-5) Inhalation LC50Rat 658 mg/L 4 h Immediate Effects Causes serious eye irritation. May cause damage to organs. May cause respiratory irritation. May cause drowsiness or dizziness.

#### Delayed Effects

Suspected of damaging fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

#### Irritation/Corrosivity Data

Causes serious eye irritation. May cause respiratory irritation.

#### Respiratory Sensitization

No information available for the product.

#### Dermal Sensitization

No information available for the product.

#### Component Carcinogenicity

Acetone (67-64-1)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

#### Germ Cell Mutagenicity

No information available for the product.

#### Reproductive Toxicity

Suspected of damaging fertility or the unborn child.

#### Specific Target Organ Toxicity - Single Exposure

heart, respiratory tract, central nervous system

#### Specific Target Organ Toxicity - Repeated Exposure

blood

#### Aspiration hazard

No information available for the product.

#### Medical Conditions Aggravated by Exposure

respiratory disorders, heart disorders, central nervous system disorders, blood system disorders

## Section 12. Ecological Information

#### Component Analysis - Aquatic Toxicity

Acetone (67-64-1)

Fish:

LC50 96 h *Oncorhynchus mykiss* 4.74 - 6.33 mg/L

LC50 96 h *Pimephales promelas* 6210 - 8120 mg/L [static]

LC50 96 h *Lepomis macrochirus* 8300 mg/L

Invertebrate:

EC50 48 h *Daphnia magna* 10294 - 17704 mg/L [static] EPA

EC50 48 h *Daphnia magna* 12600 - 12700 mg/L IUCLID

## Section 13. Disposal

## Disposal Methods

Dispose of contents/container in accordance with local/regional/national /international regulations. Do not allow to enter into ground-water, surface water or drains.

## Section 14. Transport Information

UN Number	1950
UN Proper Shipping Name	AEROSOLS
DOT Classification	Hazard Class: 2.1 Required Label(s): 2.1
Packing Group	N/A
IATA Information	Shipping Name: AEROSOLS, FLAMMABLE Hazard Class: 2.1 UN#: UN1950 Required Label(s): 2.1
ICAO Information	Shipping Name: AEROSOLS, FLAMMABLE Hazard Class: 2.1 UN#: UN1950 Required Label(s): 2.1
IMDG Information	Shipping Name: AEROSOLS Hazard Class: 2.1 UN#: UN1950 Required Label(s): 2.1
TDG Information	Shipping Name: AEROSOLS Hazard Class: 2.1 UN#: UN1950 Required Label(s): 2.1

## Section 15. Regulatory Information

U.S. Federal Regulations	<p>This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.</p> <p>Acetone (67-64-1) CERCLA: 5000 lb final RQ; 2270 kg final RQ</p> <p>SARA Section 311/312 (40 CFR 370 Subparts B and C) Acute Health: Yes Chronic Health: Yes Fire: Yes Pressure: Yes Reactivity: No</p>
U.S. State Regulations	<p>The following components appear on one or more of the following state hazardous substances lists:</p> <p>Acetone (67-64-1) CA, MA, MN, NJ, PA Propane (74-98-6) MA, MN, NJ, PA Isobutane (75-28-5) MA, NJ, PA</p>

## Section 16. Other Information

Revision Date 10/23/2019

HMIS and NFPA Rating

HMIS  
Health: 3\*  
Fire: 4  
Reactivity: 1

NFPA  
Health: 2  
Fire: 4  
Reactivity: 1

Hazard Scale:  
0 = Minimal  
1 = Slight  
2 = Moderate  
3 = Serious  
4 = Severe  
\* = Chronic hazard

### Disclaimer

The data contained herein is based upon information that Soudal believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.