

SCS9000 BLACK-03

SAFETY DATA SHEET

Classified in accordance with 29 CFR 1910.1200

1. Identification

Product identifier: SCS9000 BLACK-03

Other means of identification

Synonyms: ALKOXY SEALANT (black)

Recommended use and restriction on use

Recommended use: Sealant

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information : Momentive Performance Materials USA LLC
2750 Balltown Road,
Niskayuna, NY 12309

Contact person : commercial.services@momentive.com

Telephone : General information
+1-800-295-2392

Emergency telephone number

Supplier : CHEMTREC
1-800-424-9300

2. Hazard(s) identification

Hazard Classification

Not classified

Label Elements

Hazard Symbol: No symbol

Signal Word: No signal word.

Hazard Statement: Not applicable

Precautionary Statements : Not applicable

Hazard(s) not otherwise classified (HNOC): None.

SDS_US

SCS9000 BLACK-03

Substance(s) formed under the conditions of use: Generates methanol during cure.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*	Notes
Limestone	1317-65-3	20 - <50%	# This substance has workplace exposure limit(s).
Treated Filler	68611-44-9	1 - <5%	# This substance has workplace exposure limit(s).
(1) Carbon Black	1333-86-4	0.1 - <1%	# This substance has workplace exposure limit(s).
Octadecanoic acid	57-11-4	0.1 - <1%	# This substance has workplace exposure limit(s).
(1) QUARTZ	14808-60-7	0.1 - <1%	# This substance has workplace exposure limit(s).

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

(1) The respirable particle(s) listed above are inextricably bound within the polymer matrix, and therefore does not present an inhalation hazard during normal use of this product. Tooling or machining of the cured product (sanding, cutting, milling) may release hazardous, respirable substances.

4. First-aid measures

General information:	No action shall be taken involving any personal risk or without suitable training.
Ingestion:	If swallowed, do NOT induce vomiting. Give a glass of water.
Inhalation:	If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.
Skin Contact:	To clean from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water. If skin irritation occurs: Get medical advice/attention.

SCS9000 BLACK-03

Eye contact: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

Most important symptoms/effects, acute and delayed

Symptoms: Treatment is symptomatic and supportive.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: This product reacts with moisture in the acid contents of the stomach to form methanol. Treatment is symptomatic and supportive.

5. Fire-fighting measures

General Fire Hazards: Use standard firefighting procedures and consider the hazards of other involved materials. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: All standard extinguishing agents are suitable.

Unsuitable extinguishing media: Avoid water in straight hose stream; will scatter and spread fire.

Specific hazards arising from the chemical: In case of fire, carbon monoxide and carbon dioxide may be formed. Acute overexposure to the products of combustion may result in irritation of the respiratory tract. Reacts with water liberating small amounts of methanol. This material is reactive with water, but the reaction will not significantly increase the fire severity.

Special protective equipment and precautions for fire-fighters

Special fire-fighting procedures: Move container from fire area if it can be done without risk. Cool fire-endangered containers with water.

Special protective equipment for fire-fighters: Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. Accidental release measures

SCS9000 BLACK-03

Personal precautions, protective equipment and emergency procedures:

Keep container closed. Avoid contact with skin and eyes. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the finger and hands. Product releases methanol during application and curing. Keep out of reach of children. See Section 8 of the SDS for Personal Protective Equipment.

Methods and material for containment and cleaning up:

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wear proper protective equipment as specified in the protective equipment section.

7. Handling and storage

Precautions for safe handling: Sensitivity to static discharge is not expected.

Conditions for safe storage, including any incompatibilities: Keep away from heat, sparks and open flame. Keep container tightly closed.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Limestone - Respirable.	REL	5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
Limestone - Total	REL	10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
Limestone - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Limestone - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Limestone - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
Limestone - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
Limestone - Total dust.	TWA	15 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
Limestone - Respirable fraction.	TWA	5 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
Limestone - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Limestone - Respirable particles.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Limestone - Respirable fraction.	TWA PEL	5 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (12 2017)
Limestone - Total dust.	TWA PEL	10 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (12 2017)
Limestone - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Limestone - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as

SCS9000 BLACK-03

Limestone - Respirable fraction.	TWA	5 mg/m3	amended (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Limestone - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Treated Filler	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Treated Filler - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Treated Filler - Respirable particles.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Treated Filler	REL	6 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2019)
	IDLH	3,000 mg/m3	US. NIOSH: Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2019)
Treated Filler - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
Treated Filler - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
Treated Filler - Total dust.	TWA	15 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (01 2019)
Treated Filler - Respirable fraction.	TWA	5 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (01 2019)
Treated Filler - Total dust.	TWA PEL	10 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (12 2017)
Treated Filler - Respirable fraction.	TWA PEL	5 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (12 2017)
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Treated Filler - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Treated Filler - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
(1) Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2015)
(1) Carbon Black	REL	0.1 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	REL	3.5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended (2010)
	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	3.5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
(1) Carbon Black - Particulate.	ST ESL	35 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
	AN ESL	3.5 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)
(1) Carbon Black -	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as

SCS9000 BLACK-03

Respirable fraction.			amended (09 2016)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
(1) Carbon Black - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
(1) Carbon Black	IDLH	1,750 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
	REL	3.5 mg/m3	US. NIOSH. Pocket Guide to Chemical Hazards, as amended (2005)
	TWA PEL	3.5 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (09 2006)
	TWA	3.5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	3.5 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (06 2008)
(1) Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (12 2010)
(1) Carbon Black - as PAHs	REL	0.1 mg/m3	US. NIOSH. Pocket Guide to Chemical Hazards, as amended (2016)
Octadecanoic acid - Respirable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2017)
Octadecanoic acid - Inhalable fraction.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2017)
(1) QUARTZ - Respirable dust.	REL	0.05 mg/m3	US. NIOSH. Pocket Guide to Chemical Hazards, as amended (2010)
(1) QUARTZ - Respirable dust.	TWA	0.05 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
	OSHA_ACT	0.025 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
(1) QUARTZ - Respirable dust.	PEL	0.05 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (03 2016)
	TWA	0.1 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended (1989)
(1) QUARTZ - Particulate.	AN ESL	0.27 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (11 2016)
(1) QUARTZ - Respirable dust.	TWA PEL	0.05 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants, as amended (10 2016)
(1) QUARTZ - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
(1) QUARTZ	IDLH	50 mg/m3	US. NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended (10 2017)
(1) QUARTZ - Respirable dust.	TWA	0.050 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A, as amended (01 2019)
(1) QUARTZ - Particulate.	ST ESL	14 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality), as amended (06 2018)

SCS9000 BLACK-03

(1) QUARTZ - Respirable fraction.	TWA	0.025 mg/m ³	US. ACGIH Threshold Limit Values, as amended (01 2022)
-----------------------------------	-----	-------------------------	--

This product contains one or more substances with an occupational exposure limit. However, the respirable particle(s) of this/these substance(s) are inextricably bound within the polymer matrix. Therefore, we do not expect an exposure to this/these substance(s) during normal use of this product. Tooling or machining of the cured product (sanding, cutting, milling) may release hazardous, respirable substances.

Appropriate Engineering Controls Eye wash facilities and emergency shower must be available when handling this product. Ventilation and other forms of engineering controls are preferred for controlling exposures. Respiratory protection may be needed for non-routine or emergency situations.

Individual protection measures, such as personal protective equipment

General information: Wear suitable gloves and eye/face protection.

Eye/face protection: Safety glasses with side shields

Skin Protection

Hand Protection: Rubber gloves are recommended.

Other: Wear suitable protective clothing and eye/face protection.

Respiratory Protection: If inhalation exposure is expected, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

Hygiene measures: Provide adequate ventilation. Observe good industrial hygiene practices. Avoid contact with eyes, skin, and clothing. Wash hands after handling. When using do not eat, drink or smoke.

9. Physical and chemical properties

Appearance

Physical state: solid

Form: Paste

Color: Black

Odor: No data available.

Odor threshold: No data available.

pH: Not applicable

Melting point/freezing point: No data available.

Initial boiling point and boiling range: No data available.

Flash Point: > 93.3 °C (estimated)

Evaporation rate: < 1

Flammability (solid, gas): No data available.

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%): No data available.

SCS9000 BLACK-03

Flammability limit - lower (%):	No data available.
Explosive limit - upper:	No data available.
Explosive limit - lower:	No data available.
Heat of combustion:	No data available.
Vapor pressure:	No data available.
Vapor density:	Negligible
Density:	ca. 1.4 g/cm ³
Relative density:	ca. 1.4
Solubility(ies)	
Solubility in water:	Insoluble
Solubility (other):	Insoluble
Partition coefficient (n-octanol/water) Log Pow:	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No decomposition if stored and applied as directed.
SADT:	No data available.
Viscosity, dynamic:	No data available.
Viscosity, kinematic:	> 7 mm ² /s (40 °C)
Minimum ignition temperature:	No data available.
VOC:	37 g/l ;

10. Stability and reactivity

Reactivity:	No dangerous reaction if used as recommended.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	Under normal conditions of storage and use, hazardous polymerization will not occur.
Conditions to avoid:	Keep away from moisture. Keep away from heat, sparks and open flame.
Incompatible Materials:	Strong Acids, Strong Bases Contact with water.
Hazardous Decomposition Products:	Carbon dioxide Silicon dioxide. Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of formaldehyde are formed due to oxidative degradation. Generates methanol during cure.

11. Toxicological information

Information on likely routes of exposure

Ingestion:	No data available.
-------------------	--------------------

SCS9000 BLACK-03

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Ingestion: No data available.

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 32,632.2 mg/kg

Specified substance(s):

Treated Filler LD 50 (Rat, No data available.): 3,160 mg/kg

Octadecanoic acid LD 50 (Rat, No data available.): > 2,000 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Inhalation

Product: Not classified for acute toxicity based on available data.

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Octadecanoic acid No skin irritation

Serious Eye Damage/Eye Irritation

Product: No data available.

SCS9000 BLACK-03

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

(1) QUARTZ Overall evaluation: 1. Carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

(1) QUARTZ Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects:

No data available.

SCS9000 BLACK-03

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Octadecanoic acid LC0 (Brachydanio rerio, 96 h): > 100 mg/l
LC0 (Leuciscus idus, 96 h): > 100 mg/l

Aquatic Invertebrates

Product: No data available.

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Octadecanoic acid LC0 (Brachydanio rerio, 4 d): > 100 mg/l
LC0 (Leuciscus idus, 4 d): > 100 mg/l

Aquatic Invertebrates

Product: No data available.

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

SCS9000 BLACK-03

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

Limestone	No data available.
Treated Filler	No data available.
(1) Carbon Black	No data available.
Octadecanoic acid	No data available.
(1) QUARTZ	No data available.

Other adverse effects: No data available.

13. Disposal considerations

General information: The generation of waste should be avoided or minimized wherever possible. Do not discharge into drains, water courses or onto the ground. See Section 8 for information on appropriate personal protective equipment.

Disposal instructions: Disposal should be made in accordance with federal, state and local regulations.

Contaminated Packaging: Dispose of as unused product.

14. Transport information

DOT
Not regulated.

IMDG
Not regulated.

IATA
Not regulated.

Special precautions for user: This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
None present or none present in regulated quantities.

SCS9000 BLACK-03

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Siloxanes and Silicones, di-Me hydroxy terminated	No OSHA Hazards Causes mild skin irritation.; Respiratory hazard.
SILOXANES AND SILICONES, DI-ME Treated Filler	No OSHA Hazards No OSHA Hazards
Methyltrimethoxysilane	Causes mild skin irritation.

CERCLA Hazardous Substance List (40 CFR 302.4):

None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Not classified

SARA 302 Extremely Hazardous Substance
None present or none present in regulated quantities.

SARA 304 Emergency Release Notification
None present or none present in regulated quantities.

SARA 311/312 Hazardous Chemical
Chemical Identity Threshold Planning Quantity

US. EPCRA (SARA Title III Section 313 Toxic Chemical Release Inventory (TRI) Reporting
None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)
None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):
None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65
No ingredient requiring a warning under CA Prop 65.

US. New Jersey Worker and Community Right-to-Know Act
Chemical Identity
Siloxanes and Silicones, di-Me hydroxy terminated

SCS9000 BLACK-03

Limestone
SILOXANES AND SILICONES, DI-ME
Treated Filler
Methyltrimethoxysilane
(1) Carbon Black
(1) QUARTZ

US. Massachusetts RTK - Substance List

Chemical Identity

Treated Filler
(1) QUARTZ

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Limestone
Treated Filler
(1) Carbon Black

US. Rhode Island RTK

Chemical Identity

Treated Filler

SCS9000 BLACK-03

Inventory Status:

Australia AICS:	y (positive listing)	Remarks: None.
EU EINECS List:	y (positive listing)	Remarks: None.
Japan (ENCS) List:	n (negative listing)	Remarks: None.
China Inv. Existing Chemical Substances:	y (positive listing)	Remarks: None.
Korea Existing Chemicals Inv. (KECI):	y (positive listing)	Remarks: None.
Canada DSL Inventory List:	y (positive listing)	Remarks: None.
Canada NDSL Inventory:	n (negative listing)	Remarks: None.
Philippines PICCS:	y (positive listing)	Remarks: None.
US TSCA Inventory:	y (positive listing)	Remarks: On TSCA Inventory
Taiwan Chemical Substance Inventory:	y (positive listing)	Remarks: None.

16. Other information, including date of preparation or last revision

HMIS Hazard ID

Health	<input type="text" value="0"/>
Flammability	<input type="text" value="0"/>
Physical Hazards	<input type="text" value="1"/>
PERSONAL PROTECTION	<input type="text"/>

Hazard rating: 0 - Minimal; 1 - Slight; 2 - Moderate; 3 - Serious; 4 - Severe; RNP - Rating not possible; *Chronic health effect

Issue Date: 03/09/2023

Revision Date: No data available.

Version #: 3.1

Further Information: No data available.

SCS9000 BLACK-03

Disclaimer:

Notice to reader

Unless otherwise specified in section 1, Momentive products are intended for use in the manufacture and/or formulation of products and are not intended for direct consumer use. These products are not intended for long-lasting (> 30 days) implantation, injection or direct ingestion into the human body, nor for use in the manufacture of multiple use contraceptives. Keep out of the reach of children.

Further Information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

® and TM indicate trademarks owned by or licensed to Momentive.