



Version number: 2.0 Revision: 2025-04-07 Replaces version of: 2025-03-28 (1)

SECTION 1: Identification

1.1 Product identifier

Trade name Pure Polish

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Vehicle polishing compound

Professional use Industrial use

1.3 Details of the distributor

Interchem Limited 9th Avenue South, Barataria, Trinidad.

Telephone: 1(868) 235-2436
E-mai sales@interchem.co.tt
Website: www.interchem.co.tt

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Cat- egory	Hazard class and category	Hazard statement
A.2	skin corrosion/irritation	2	Skin Irrit. 2	H315

For full text of abbreviations: see SECTION 16.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word warning

- Pictograms

GHS07



- Hazard statements

H315 Causes skin irritation.

United States: en Page: 1 / 18





Version number: 2.0 Revision: 2025-04-07 Replaces version of: 2025-03-28 (1)

- Precautionary statements

P280 Wear protective gloves.

P302+P352 If on skin: Wash with plenty of water.
P321 Specific treatment (see on this label).

P332+P313 If skin irritation occurs: Get medical advice/attention.
P362 Take off contaminated clothing and wash before reuse.

2.3 Other hazards

Special danger of slipping by leaking/spilling product.

Hazards not otherwise classified

Harmful to aquatic life with long lasting effects (GHS category 3: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of \geq 0.1%.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Hazardous ingredients acc. to GHS							
Name of substance	Identifier	Wt%	Classification acc. to GHS	Notes			
odorless mineral spirits	CAS No 64742-48-9	12 - < 20	Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226				
distillates (petroleum) hy- drotreated, light	CAS No 64742-47-8	5 – < 10	Asp. Tox. 1 / H304				
White mineral oil (petro- leum)	CAS No 8042-47-5	1-<5	Asp. Tox. 1 / H304				

Remarks

For full text of abbreviations: see SECTION 16. Exact percentage of ingredients is withheld as a trade secret. This table, if present, includes all GHS classified ingredients present above their cut-off limits, even if the finished product is not classified as hazardous by GHS.

United States: en Page: 2 / 18



Version number: 2.0 Revision: 2025-04-07 Replaces version of: 2025-03-28 (1)

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

none

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal

United States: en Page: 3 / 18



Version number: 2.0 Revision: 2025-04-07 Replaces version of: 2025-03-28 (1)

binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Control of the effects

Protect against external exposure, such as frost

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occup	Occupational exposure limit values (Workplace Exposure Limits)										
Cou ntry	Name of agent	CAS No	Iden tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sourc e
US	alpha-alumina	1344-28- 1	REL							appx- D	NIOS H REL
US	alpha-alumina	1344-28- 1	PEL		15					dust	29 CFR 1910. 1000
US	alpha-alumina	1344-28- 1	PEL		5					r	29 CFR 1910. 1000
US	aluminium, in-	1344-28-	TLV®		1					r	AC-

United States: en Page: 4 / 18





1910. 1000

29

CFR

1910. 1000 AC-

GIH®

2024

i, ex-Met-

Work

Fl



Pure Polish

Version number: 2.0 Revision: 2025-04-07 Replaces version of: 2025-03-28 (1)

Occupational exposure limit values (Workplace Exposure Limits)

	•										
Cou ntry	Name of agent	CAS No	Iden tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sourc e
	soluble com- pounds	1									GIH® 2024
US	aluminium ox- ide	1344-28- 1	PEL (CA)		10					dust	Cal/O SHA PEL
US	aluminium ox- ide	1344-28- 1	PEL (CA)		5					r	Cal/O SHA PEL
US	glycerine	56-81-5	REL							mist, appx- D	NIOS H REL
US	glycerine	56-81-5	PEL		15					mist, dust	29 CFR 1910. 1000
US	glycerine	56-81-5	PEL		5					mist,	29 CER

2,000

5

Notation

US

US

appx-D see Appendix D - Substances with No Established RELs

64742-

48-9

8042-47-

PEL

TLV®

500

 $\label{eq:ceiling-C} \text{Ceiling value is a limit value above which exposure should not occur}$

dust as dust

exMetWork- excluding metal working fluids

petroleum distil-

lates (naphtha)

(rubber solvent)

mineral oil

Fl

inhalable fraction

mist as mists r respirable fraction

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute peri-

od (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours

time-weighted average (unless otherwise specified

United States: en Page: 5 / 18



acc. to 29 CFR 1910.1200 App D

Pure Polish

Version number: 2.0 Revision: 2025-04-07 Replaces version of: 2025-03-28 (1)

Relevant DNELs of components								
Name of sub- stance	CAS No	End- point	Threshol d level	Protection goal, route of exposure	Used in	Exposure time		
White mineral oil (petroleum)	8042-47-5	DNEL	165 mg/m ³	human, inhalat- ory	worker (industry)	chronic - systemic effects		
White mineral oil (petroleum)	8042-47-5	DNEL	217 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects		

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid (viscous)
Color	light grey
Particle	not relevant (liquid)
Odor	characteristic

United States: en Page: 6 / 18





Version number: 2.0 Revision: 2025-04-07 Replaces version of: 2025-03-28 (1)

Other safety parameters

pH (value)	8 – 8.5 (25 °C)
Melting point/freezing point	not determined
Initial boiling point and boiling range	100 °C
Flash point	>100 °C at 101 kPa >212 °C at 1 atm
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)

Explosive limits

- Lower explosion limit (LEL)	0.6 vol%
- Upper explosion limit (UEL)	19 vol%
Vapor pressure	32 hPa at 25 °C
Density	1 ^g / _{ml} at 25 °C
Vapor density	this information is not available
Relative density	1 at 25 °C (water = 1)
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	262 °C (auto-ignition temperature (liquids and gases))

Viscosity

- Kinematic viscosity	10,386 ^{mm²} / _s at 25 °C
- Dynamic viscosity	10,500 cP at 25 °C
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Temperature class (USA, acc. to NEC 500)	T2B (maximum permissible surface temperature on the equipment: 260°C)
--	---

United States: en Page: 7 / 18





Version number: 2.0 Revision: 2025-04-07 Replaces version of: 2025-03-28 (1)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
White mineral oil (petroleum)	8042-47-5	dermal	>2,000 ^{mg} / _{kg}
White mineral oil (petroleum)	8042-47-5	inhalation: dust/mist	>5 ^{mg} / _l /4h

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

United States: en Page: 8 / 18





Version number: 2.0 Revision: 2025-04-07 Replaces version of: 2025-03-28 (1)

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans				
Name of substance	CAS No	Classification	Remarks	Number
distillates (petroleum) hydro- treated, light	8002-05-9	3		
odorless mineral spirits	8002-05-9	3		

<u>Legend</u>

3 Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
odorless mineral spir- its	64742-48-9	LL50	8.2 ^{mg} / _l	fish	96 h
odorless mineral spir- its	64742-48-9	EL50	4.5 ^{mg} / _l	aquatic invertebrates	48 h
White mineral oil (pet- roleum)	8042-47-5	LL50	>10,000 ^{mg} / _l	fish	96 h

Aquatic toxicity (chronic) of components CAS No Exposure time Name of substance Value **Endpoint Species** 10 ^{mg}/_I odorless mineral spir-64742-48-9 **EL50** fish 21 d 15 ^{mg}/_I odorless mineral spir-64742-48-9 EC50 microorganisms 40 h

12.2 Persistence and degradability

Data are not available.

United States: en Page: 9 / 18





Version number: 2.0 Revision: 2025-04-07 Replaces version of: 2025-03-28 (1)

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of \geq 0.1%.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of \geq 0.1%.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1	UN number	not subject to transport regulations

14.2 UN proper shipping name not relevant

14.3 Transport hazard class(es) none

14.4 Packing group not assigned

14.5 Environmental hazards non-environmentally hazardous acc. to the dan-

gerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT)

Not subject to transport regulations.

International Maritime Dangerous Goods Code (IMDG)

Not subject to IMDG.

United States: en Page: 10 / 18





Version number: 2.0 Revision: 2025-04-07 Replaces version of: 2025-03-28 (1)

International Civil Aviation Organization (ICAO-IATA/DGR)

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
water	7732-18-5	solvent	
aluminium oxide	1344-28-1	abrasive	
odorless mineral spirits	64742-48-9	solvents	Canada PBiTs EC Annex VI CMRs - Cat. 1B
odorless mineral spirits	8002-05-9		ATSDR Neurotoxicants Canada PBiTs EC Annex VI CMRs - Cat. 1B
distillates (petroleum) hydrotreated, light	64742-47-8	solvents	
Glycerine	56-81-5	humectant	
White mineral oil (petroleum)	8042-47-5	lubricant	
C11-15, Pareth-9	84133-50-6	surfactant	
acrylate copolymer	75760-37-1	viscosity modifier	
N,N-bis(2-Hydroxyethyl)oleamide	93-83-4	surfactant	
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	solvents	EC Annex VI CMRs - Cat. 1B
Distillates (petroleum), hydrotreated heavy naphthenic	8002-05-9		ATSDR Neurotoxicants Canada PBiTs EC Annex VI CMRs - Cat. 1B

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
distillates (petroleum) hydrotreated, light	8002-05-9	A, O, R, T, *	
odorless mineral spirits	64742-48-9	A, O	
odorless mineral spirits	8002-05-9	A, O, R, T, *	

United States: en Page: 11 / 18



Version number: 2.0 Revision: 2025-04-07 Replaces version of: 2025-03-28 (1)

<u>Legend</u>

- * Substances which are regulated by OSHA as carcinogens; have been categorized by the ACGIH as either "human carcinogens" or "suspect of carcinogenic potential for man"; have been evaluated by the International Agency for Research on Cancer (IARC) and found to be carcinogens or potential carcinogens; or have been listed as a carcinogen or potential carcinogen in the Annual Report on Carcinogens published by the National Toxicology Program (NTP).
- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division
- R International Agency for Research on Cancer (IARC) Monographs on the Evaluation of the Carcinogenic Risks to Humans; Overall Evaluations of Carcinogenicity: An Updating of IARC Monographs Volumes 1 to 42, Supplement 7 (1987). Available from: WHO Publications Centre USA
- T National Toxicology Program (NTP) "Fifth Annual Report on Carcinogens," 1989 (NTP 89-239). Order information: (919) 541-3992

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
distillates (petroleum) hydrotreated, light	8002-05-9		F3
odorless mineral spirits	8002-05-9		F3

Legend

F3 Flammable - Third Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
PETROLEUM	8002-05-9	
PETROLEUM	8002-05-9	

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
distillates (petroleum) hydrotreated, light	8002-05-9	F
odorless mineral spirits	8002-05-9	F

Legend

F Flammability (NFPA®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals				
Name acc. to inventory	CAS No	Conc.	Remarks	Type of the toxicity
carbon black	1333-86-4	0.004 wt%	airborne, unbound particles of respirable size	cancer
diethanolamine	111-42-2	0.025 wt%		cancer

United States: en Page: 12 / 18





Version number: 2.0 Revision: 2025-04-07 Replaces version of: 2025-03-28 (1)

Proposition 65 List of chemicals				
Name acc. to inventory	CAS No	Conc.	Remarks	Type of the toxicity
1,4-dioxane	123-91-1	0.000003 wt%		cancer

VOC content

Regulated Volatile Organic Compounds (VOC-EPA)
 Regulated Volatile Organic Compounds (VOC-Cal ARB)
 14 %

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	/	none
Health	2	temporary or minor injury may occur
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

Chronic: chronic hazard
Flammability: flammability hazards
Health: health hazard

Personal protection: personal protective equipment (PPE) for normal use

Physical hazard: reactivity

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

United States: en Page: 13 / 18



Version number: 2.0 Revision: 2025-04-07 Replaces version of: 2025-03-28 (1)

National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)
AU	AIIC	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed

Legend

AIIC Australian Inventory of Industrial Chemicals
CICR Chemical Inventory and Control Regulation

CSCL-ENCS List of Existing and New Chemical Substances (CSCL-ENCS)

DSL Domestic Substances List (DSL)

ECSI EC Substance Inventory (EINECS, ELINCS, NLP)

IECSC Inventory of Existing Chemical Substances Produced or Imported in China

INSQ National Inventory of Chemical Substances

ISHA-ENCS Inventory of Existing and New Chemical Substances (ISHA-ENCS)

KECI Korea Existing Chemicals Inventory NZIOC New Zealand Inventory of Chemicals

PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)

REACH Reg. REACH registered substances
TCSI Taiwan Chemical Substance Inventory

TSCA Toxic Substance Control Act

Additional information

The contained substances are listed in the following national inventories: AICiS (Australia)
DSL/NDSL (Canada)
IECSC (China)
KECL (Republic of Korea)
PICCS (Philippines)
TCSI (Taiwan)
TSCA (United States)

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

United States: en Page: 14 / 18





Version number: 2.0 Revision: 2025-04-07 Replaces version of: 2025-03-28 (1)

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Alignment to regulation: Globally Harmonized System of Classification and Labelling of Chemicals ("Purple book"). Restructuring: section 9, section 14

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3		Hazards not otherwise classified	yes
2.3		Hazards not otherwise classified: change in the listing (table)	yes
3.2		Hazardous ingredients acc. to GHS: change in the listing (table)	yes
6.2	Environmental precautions: not required	Environmental precautions	yes
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)	yes
9.1	pH (value): not determined	pH (value): 8 – 8.5 (25 °C)	yes
9.1	Auto-ignition temperature: >220 °C (auto-ignition temperature (liquids and gases))	Auto-ignition temperature: 262 °C (auto-ignition temperature (liquids and gases))	yes
9.2	Temperature class (USA, acc. to NEC 500): T2D (maximum permissible surface temperat- ure on the equipment: 215°C)	Temperature class (USA, acc. to NEC 500): T2B (maximum permissible surface temperat- ure on the equipment: 260°C)	yes
11.1		Acute toxicity estimate (ATE) of components: change in the listing (table)	yes
11.1		IARC Monographs on the Evaluation of Carcino- genic Risks to Humans: change in the listing (table)	yes
12.1	Toxicity: Shall not be classified as hazardous to the aquatic environment.	Toxicity: Harmful to aquatic life with long lasting effects.	yes
12.1		Aquatic toxicity (acute) of components: change in the listing (table)	yes
12.1		Aquatic toxicity (chronic) of components: change in the listing (table)	yes
15.1		Cleaning Product Right to Know Act Substance List (CA-RTK): change in the listing (table)	yes
15.1		Hazardous Substances List (MN-ERTK): change in the listing (table)	yes
15.1		Hazardous Substance List (NJ-RTK)	yes
15.1		Hazardous Substance List (NJ-RTK): change in the listing (table)	yes
15.1		Hazardous Substance List (Chapter 323) (PA- RTK)	yes

United States: en Page: 15 / 18







Version number: 2.0 Revision: 2025-04-07 Replaces version of: 2025-03-28 (1)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
15.1		Hazardous Substance List (Chapter 323) (PA- RTK): change in the listing (table)	yes
15.1		Hazardous Substance List (RI-RTK)	yes
15.1		Hazardous Substance List (RI-RTK): change in the listing (table)	yes
15.1		NPCA-HMIS® III: change in the listing (table)	yes
15.1		National inventories: change in the listing (table)	yes
15.1	Additional information: The contained substances are listed in the fol- lowing national inventories: DSL/NDSL (Canada) TCSI (Taiwan) TSCA (United States)	Additional information: The contained substances are listed in the following national inventories: AICIS (Australia) DSL/NDSL (Canada) IECSC (China) KECL (Republic of Korea) PICCS (Philippines) TCSI (Taiwan) TSCA (United States)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH® 2024	From ACGIH®, 2024 TLVs® and BEIs® Book. Copyright 2024. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50%

United States: en Page: 16 / 18





Version number: 2.0 Revision: 2025-04-07 Replaces version of: 2025-03-28 (1)

ELINCS European List of Notified Chemical Substances EPA Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment Flam. Liq. Flammable liquid GHS "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations IARC International Agency for Research on Cancer IATA International Air Transport Association IATA/DGR Dangerous Goods Regulations (DGR) for the air transport (IATA) ICAO International Civil Aviation Organization IMDG International Maritime Dangerous Goods Code LL50 Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality NFPA® National Fire Protection Association (United States) NIOSH REL National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs) NLP No-Longer Polymer NPCA-HMIS® III National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition OSHA Occupational Safety and Health Administration (United States) PBT Persistent, Bioaccumulative and Toxic PEL Permissible exposure limit ppm Parts per million Skin Corr. Corrosive to skin Skin Irrit. Irritant to skin STEL Specific target organ toxicity - single exposure TLV® Threshold Limit Values TVA Time-weighted average VOC Volatile Organic Compounds Very Persistent and very Bioaccumulative	Abbr.	Descriptions of used abbreviations
ELINCS European List of Notified Chemical Substances EPA Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment Flam. Liq. Flammable liquid GHS "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations JARC International Agency for Research on Cancer IATA International Air Transport Association IATA/DGR Dangerous Goods Regulations (DGR) for the air transport (IATA) ICAO International Civil Aviation Organization IMDG International Maritime Dangerous Goods Code LL50 Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality NFPA® National Fire Protection Association (United States) NIOSH REL National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs) NLP NO-Longer Polymer NPCA-HMIS® III National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition OSHA Occupational Safety and Health Administration (United States) PBT Persistent, Bioaccumulative and Toxic PEL Permissible exposure limit Skin Corr. Corrosive to skin Skin Irrit. Irritant to skin STEL Short-term exposure limit STOT SE Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	Abbr.	
EPA Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment Flam. Liq. Flammable liquid GHS "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations IARC International Agency for Research on Cancer IATA International Air Transport Association IATA/DGR Dangerous Goods Regulations (DGR) for the air transport (IATA) ICAO International Civil Aviation Organization IMDG International Maritime Dangerous Goods Code LL50 Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality NFPA® National Fire Protection Association (United States) NIOSH REL National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs) NLP No-Longer Polymer NPCA-HMIS® III National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition OSHA Occupational Safety and Health Administration (United States) PBT Persistent, Bioaccumulative and Toxic PEL Permissible exposure limit ppm Parts per million Skin Corr. Corrosive to skin Skin Irrit, Irritant to skin STEL Short-term exposure limit STOT SE Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds		
Flam. Liq. Flammable liquid GHS "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations IARC International Agency for Research on Cancer IATA International Air Transport Association IATA/DGR Dangerous Goods Regulations (DGR) for the air transport (IATA) ICAO International Civil Aviation Organization IMDG International Maritime Dangerous Goods Code LL50 Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality NFPA® National Fire Protection Association (United States) NIOSH REL National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs) NLP No-Longer Polymer NPCA-HMIS® III National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition OSHA Occupational Safety and Health Administration (United States) PBT Persistent, Bioaccumulative and Toxic PEL Permissible exposure limit ppm Parts per million Skin Corr. Corrosive to skin Stin Irrit. Irritant to skin STEL Short-term exposure limit STOT SE Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	ELINCS	·
GHS "Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations IARC International Agency for Research on Cancer IATA International Air Transport Association IATA/DGR Dangerous Goods Regulations (DGR) for the air transport (IATA) ICAO International Maritime Dangerous Goods Code LL50 Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality NFPA® National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs) NLP No-Longer Polymer NPCA-HMIS® III National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition OSHA Occupational Safety and Health Administration (United States) PBT Persistent, Bioaccumulative and Toxic PEL Permissible exposure limit ppm Parts per million Skin Corr. Corrosive to skin Skin Irrit, Irritant to skin STEL Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
IARC International Agency for Research on Cancer IATA International Air Transport Association IATA/DGR Dangerous Goods Regulations (DGR) for the air transport (IATA) ICAO International Civil Aviation Organization IMDG International Maritime Dangerous Goods Code LL50 Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality NFPA® National Fire Protection Association (United States) NIOSH REL National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs) NLP No-Longer Polymer NPCA-HMIS® III National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition OSHA Occupational Safety and Health Administration (United States) PBT Persistent, Bioaccumulative and Toxic PEL Permissible exposure limit ppm Parts per million Skin Corr. Corrosive to skin Skin Irrit. Irritant to skin STEL Short-term exposure limit STOT SE Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	Flam. Liq.	Flammable liquid
IATA International Air Transport Association IATA/DGR Dangerous Goods Regulations (DGR) for the air transport (IATA) ICAO International Civil Aviation Organization IMDG International Maritime Dangerous Goods Code LL50 Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality NFPA® National Fire Protection Association (United States) NIOSH REL National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs) NLP No-Longer Polymer NPCA-HMIS® III National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition OSHA Occupational Safety and Health Administration (United States) PBT Persistent, Bioaccumulative and Toxic PEL Permissible exposure limit ppm Parts per million Skin Corr. Corrosive to skin Skin Irrit. Irritant to skin STEL Short-term exposure limit STOT SE Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	GHS	
IATA/DGR Dangerous Goods Regulations (DGR) for the air transport (IATA) ICAO International Civil Aviation Organization IMDG International Maritime Dangerous Goods Code LL50 Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality NFPA® National Fire Protection Association (United States) NIOSH REL National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs) NLP No-Longer Polymer NPCA-HMIS® III National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition OSHA Occupational Safety and Health Administration (United States) PBT Persistent, Bioaccumulative and Toxic PEL Permissible exposure limit ppm Parts per million Skin Corr. Corrosive to skin Skin Irrit. Irritant to skin STEL Short-term exposure limit STOT SE Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	IARC	International Agency for Research on Cancer
ICAO International Civil Aviation Organization IMDG International Maritime Dangerous Goods Code LL50 Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality NFPA® National Fire Protection Association (United States) NIOSH REL National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs) NLP No-Longer Polymer NPCA-HMIS® III National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition OSHA Occupational Safety and Health Administration (United States) PBT Persistent, Bioaccumulative and Toxic PEL Permissible exposure limit ppm Parts per million Skin Corr. Corrosive to skin Skin Irrit. Irritant to skin STEL Short-term exposure limit STOT SE Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	IATA	International Air Transport Association
IMDG International Maritime Dangerous Goods Code LL50 Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality NFPA® National Fire Protection Association (United States) NIOSH REL National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs) NLP No-Longer Polymer NPCA-HMIS® III National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition OSHA Occupational Safety and Health Administration (United States) PBT Persistent, Bioaccumulative and Toxic PEL Permissible exposure limit ppm Parts per million Skin Corr. Corrosive to skin Skin Irrit. Irritant to skin STEL Short-term exposure limit STOT SE Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
LL50 Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality NFPA® National Fire Protection Association (United States) NIOSH REL National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs) NLP No-Longer Polymer NPCA-HMIS® III National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition OSHA Occupational Safety and Health Administration (United States) PBT Persistent, Bioaccumulative and Toxic PEL Permissible exposure limit ppm Parts per million Skin Corr. Corrosive to skin Skin Irrit. Irritant to skin STEL Short-term exposure limit STOT SE Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	ICAO	International Civil Aviation Organization
NFPA® National Fire Protection Association (United States) NIOSH REL National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs) NLP No-Longer Polymer NPCA-HMIS® III National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition OSHA Occupational Safety and Health Administration (United States) PBT Persistent, Bioaccumulative and Toxic PEL Permissible exposure limit ppm Parts per million Skin Corr. Corrosive to skin Skin Irrit. Irritant to skin STEL Short-term exposure limit STOT SE Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	IMDG	International Maritime Dangerous Goods Code
NIOSH REL National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs) NLP No-Longer Polymer NPCA-HMIS® III National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition OSHA Occupational Safety and Health Administration (United States) PBT Persistent, Bioaccumulative and Toxic PEL Permissible exposure limit ppm Parts per million Skin Corr. Corrosive to skin Skin Irrit. Irritant to skin STEL Short-term exposure limit STOT SE Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
NPCA-HMIS® III National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition OSHA Occupational Safety and Health Administration (United States) PBT Persistent, Bioaccumulative and Toxic PEL Permissible exposure limit ppm Parts per million Skin Corr. Corrosive to skin Skin Irrit. Irritant to skin STEL Short-term exposure limit STOT SE Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	NFPA®	National Fire Protection Association (United States)
NPCA-HMIS® III National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition OSHA Occupational Safety and Health Administration (United States) PBT Persistent, Bioaccumulative and Toxic PEL Permissible exposure limit ppm Parts per million Skin Corr. Corrosive to skin Skin Irrit. Irritant to skin STEL Short-term exposure limit STOT SE Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
OSHA Occupational Safety and Health Administration (United States) PBT Persistent, Bioaccumulative and Toxic PEL Permissible exposure limit ppm Parts per million Skin Corr. Corrosive to skin Skin Irrit. Irritant to skin STEL Short-term exposure limit STOT SE Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	NLP	No-Longer Polymer
PBT Persistent, Bioaccumulative and Toxic PEL Permissible exposure limit ppm Parts per million Skin Corr. Corrosive to skin Skin Irrit. Irritant to skin STEL Short-term exposure limit STOT SE Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	NPCA-HMIS® III	
PEL Permissible exposure limit ppm Parts per million Skin Corr. Corrosive to skin Skin Irrit. Irritant to skin STEL Short-term exposure limit STOT SE Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	OSHA	Occupational Safety and Health Administration (United States)
ppm Parts per million Skin Corr. Corrosive to skin Skin Irrit. Irritant to skin STEL Short-term exposure limit STOT SE Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	PBT	Persistent, Bioaccumulative and Toxic
Skin Corr. Skin Irrit. Irritant to skin STEL Short-term exposure limit STOT SE Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	PEL	Permissible exposure limit
Skin Irrit. STEL Short-term exposure limit STOT SE Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	ppm	Parts per million
STEL Short-term exposure limit STOT SE Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	Skin Corr.	Corrosive to skin
STOT SE Specific target organ toxicity - single exposure TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	Skin Irrit.	Irritant to skin
TLV® Threshold Limit Values TWA Time-weighted average VOC Volatile Organic Compounds	STEL	Short-term exposure limit
TWA Time-weighted average VOC Volatile Organic Compounds	STOT SE	Specific target organ toxicity - single exposure
VOC Volatile Organic Compounds	TLV®	Threshold Limit Values
5	TWA	Time-weighted average
vPvB Very Persistent and very Bioaccumulative	VOC	Volatile Organic Compounds
	vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

United States: en Page: 17 / 18



acc. to 29 CFR 1910.1200 App D

Pure Polish

Version number: 2.0 Revision: 2025-04-07 Replaces version of: 2025-03-28 (1)

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United States: en Page: 18 / 18