

ECONOMICAL

RECHARGEABLE

ALUMINIUM ALLOY CYLINDER

STAINLESS STEEL HEAD ASSEMBLY

EPOXY POWDER COATED FINISH

ALL METAL COMPONENTS

5 YEAR WARRANTY

TEMPERATURE RANGE - 30°C to 60°C

TITAN CARBON DIOXIDE

Portable Fire Extinguishers smother Class B and Class C fires quickly by displacing the oxygen in the air.

They are ideal for electronic and electrical rooms where other agents may cause further damage to equipment.



SPECIFICATIONS

CARBON DIOXIDE

SIZE & CAPACITY (LBS.)	5
APPLICATION	HORN
MODEL NUMBER	MT02-01
CE RATING	34B
WEIGHT (LBS.)	14.6
HEIGHT (IN.)	18.7
OUTER DIAMETER (IN.)	4.1
DISCHARGE TIME (SEC.)	10
STANDARD WALL BRACKET	YES

CLASSES OF FIRES	TYPES OF FIRES	PICTURE SYMBOL
B	Gasoline, oil, paint and other flammable liquids.	
C	May be used on fires involving live electrical equipment without danger to the operator.	

APPROVALS: CE, EN3, ISO 9001



DISTRIBUTED BY:

InterChem
Just what you need!

INTERCHEM LIMITED
9th Avenue South,
Barataria, Trinidad.
Tel.: (868) 235-CHEM (2436)
Email: sales@interchem.co.tt

Website: www.interchem.co.tt, www.titan.co.tt