

ECONOMICALLY PRICED

RECHARGEABLE

STORED PRESSURE DESIGN

EPOXY POWDER COATED FINISH

ALL METAL COMPONENTS

5 YEAR WARRANTY

TEMPERATURE RANGE -0°C to 55°C

MANUFACTURED OF DURABLE HIGH QUALITY MATERIALS

TITAN FOAM Wheeled Fire Extinguishers use AR-FFF foam at 3% solution. The AR-FFF formula provides a blanketing effect that smothers and cools both Class A & B fires, and greatly reduces flashback as it suppresses all vapours.



SPECIFICATIONS

CARBON DIOXIDE

CAPACITY	50L	100L
CYLINDER LENGTH (MM.)	875	1100
CYLINDER WEIGHT (KG.)	32	50
EXTINGUISHER WEIGHT (KG.)	95	160
FILLED WEIGHT (KG.)	50	100
OUTER DIAMETER (MM.)	320	406
VOLUME (L.)	59	124
TEMPERATURE RANGE	-0°C - 55°C	-0°C - 55°C
WORKING PRESSURE (BAR)	15	15
TEST PRESSURE (BAR)	35	35
MIN WALL-THICKNESS (MM.)	2.5	3.0
FIRE CLASS	55A 1BC	55A 3BC

CLASSES OF FIRES	TYPES OF FIRES	PICTURE SYMBOL
A	Wood, paper, cloth, trash & other ordinary materials.	
B	Gasoline, oil, paint and other flammable liquids.	

APPROVALS: CE, EN3, ISO 9001



Complies with
BS EN3

DISTRIBUTED BY:

InterChem
Just what you need!

INTERCHEM LIMITED
9th Avenue South,
Barataria, Trinidad.
Tel.: (868) 235-CHEM (2436)
Email: sales@interchem.co.tt
Website: www.interchem.co.tt, www.titan.co.tt