

# ABC Dry Chemical Wheeled Unit

**ECONOMICAL**

**RECHARGEABLE**

**CARBON STEEL CYLINDER**

**EPOXY POWDER COATED FINISH**

**ALL METAL COMPONENTS**

**TEMPERATURE RANGE -20°C to 55°C**

**TITAN ABC Dry Chemical Stored and External Pressured Wheeled Units** are manufactured to provide protection for hazardous areas where the potential for large fires exists. They can be strategically located to provide maximum protection for a wide variety of hazards, while taking up minimal space, and requiring only one trained person for operation.

This wheeled extinguisher is completely self-contained.

Some typical application include paint spray booths, dip tanks, offshore platforms, loading docks, fuel storage areas, airports and heavy manufacturing operations.



## SPECIFICATIONS

## STORED PRESSURE

CAPACITY	50kg	100kg
CYLINDER LENGTH (MM.)	875	1100
CYLINDER WEIGHT (KG.)	32	50
EXTINGUISHER WEIGHT (KG.)	93	160
FILLED WEIGHT (KG.)	50	100
OUTER DIAMETER (MM.)	320	406
VOLUME (L.)	59	124
TEMPERATURE RANGE	-20°C - 55°C	-20°C - 55°C
WORKING PRESSURE (BAR)	15	15
TEST PRESSURE (BAR)	35	35
MIN WALL-THICKNESS (MM.)	3.0	3.0
FIRE CLASS	55A 2B C	55A 3BC

CLASSES OF FIRES	TYPES OF FIRES	PICTURE SYMBOL
<b>A</b>	Wood, paper, cloth, trash & other ordinary materials.	
<b>B</b>	Gasoline, oil, paint and other flammable liquids.	
<b>C</b>	May be used on fires involving live electrical equipment without danger to the operator.	

**APPROVALS: CE, EN3, ISO 9001**



Complies with  
**BS EN3**

DISTRIBUTED BY:

**InterChem**  
Just what you need!

INTERCHEM LIMITED  
9th Avenue South,  
Barataria, Trinidad.  
Tel.: (868) 235-CHEM (2436)  
Email: sales@interchem.co.tt  
Website: www.interchem.co.tt, www.titan.co.tt