

ECONOMICALLY PRICED

RECHARGEABLE

STORED PRESSURE DESIGN



EPOXY POWDER COATED FINISH

ALL METAL COMPONENTS

5 YEAR WARRANTY

TEMPERATURE RANGE -0°C to 55°C

MANUFACTURED OF DURABLE HIGH QUALITY MATERIALS

CLASSES OF FIRES	TYPES OF FIRES	PICTURE SYMBOL
A	Wood, paper, cloth, trash & other ordinary materials.	
B	Gasoline, oil, paint and other flammable liquids.	



TITAN FOAM Wheeled Fire Extinguishers use AFFF foam at 3% solution. The AFFF formula provides a blanketing effect that smothers and cools both Class A & B fires, and greatly reduces flashback as it suppresses all vapours.

SPECIFICATIONS	FOAM WHEELED UNITS
CAPACITY	50
CYLINDER LENGTH (MM.)	875
CYLINDER WEIGHT (KG.)	32
EXTINGUISHER WEIGHT (KG.)	100
FILLED WEIGHT (KG.)	50
OUTER DIAMETER (MM.)	320
VOLUME (L.)	59
TEMPERATURE RANGE	-0°C - 55°C
WORKING PRESSURE (BAR)	0
TEST PRESSURE (BAR)	35
MIN WALL-THICKNESS (MM.)	3.0
FIRE CLASS	55A IIB

APPROVALS: CE, EN3, ISO 9001



Complies with
BS EN3

DISTRIBUTED BY:

InterChem

INTERCHEM LIMITED

♦ 9th Avenue South, Barataria, Trinidad.

♦ Tel.: (868) 638-3800

♦ Fax: (868) 638-3801

♦ Email: mail@interchem.co.tt

♦ Website: www.interchem.co.tt, www.titan.co.tt